

(43)Date of publication of application: 03.09.96

(51)Int. Cl

B23K 26/00
B23K 26/02
B23K 26/08
F01L 3/24
F02F 1/24

(21)Application number: **07033445**

(22)Date of filing: 22.02.95

(71)Applicant: **NISSAN MOTOR CO LTD**

(72)Inventor: NISHIMURA KIMIO
MATSUYAMA HIDENOBU
TAKENOUCHI MASARU

(54) BUILT-UP WELDING METHOD FOR VALVE SEAT OF CYLINDER HEAD

angle formed by the powder feeding nozzle 4 with the laser beam 3 is set to 5-20°.

(57) Abstract:

COPYRIGHT: (C)1996,JPO

PURPOSE: To stabilize powder feeding density and to eliminate deviation between a powder feeding position and an irradiation position of a laser beam on the surface of a seat.

CONSTITUTION: The seat surface 2a of a valve seat 2 is irradiated with a laser beam 3 while a powder 5 is supplied from a powder feeding nozzle 4 to the surface. The valve seat 2 is rotatably moved in the circumferential direction against the laser beam 3 to form a build-up layer 6 on the entire circumference of the seat surface 2a of the valve seat 2. The angle formed by the normal line (a) of a cross-sectionally circular-arc seat surface 2a with the powder feeding nozzle 4 is set to 0-20°, and the

